



PES

PLANT SALES & PARTS

WINGET 100TFT

General Information

- Hand-fed concrete mixers from 100 litres to 200 litres mixed batch output.
- All models capable of mixing at a rate of 12 batches per hour giving production output rates ranging from 1.2 to 2.4 cubic metres per hour.
- Robustly engineered with fully enclosed drivelines, WINGET mixers provide safe, reliable performance and long service life.
- Highly efficient, two piece heavy gauge, spun steel drum.
- Multi-position lockable drum.
- Positive, heavy duty driveline using roller chain, (belt drive on electric start) bevel wheel and pinion.
- Fast Tow trailer models available with adjustable towbar, pneumatic tyres, mudguards and independent suspension.



Capacities:

Mixed Batch Output	100 Litres
Unmixed Capacity	150 Litres
Gross Drum Volume	263 Litres
Drum Speed	22 rev/min
Production Rate	1.2m ³ / hr

Engine

Yanmar L48 Electric start

Dimensions

Length o/a	1.72/2.37m
Width o/a	1.24m
Height o/a	1.63m
Loading Height	1.06m
Discharge Height	0.60m
Machine Weight	395 kg

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Tel : 01392 882220

Email: office@pesplant.co.uk