

WINGET 150T

General Information

- Hand-fed concrete mixers from 100 litres to 200 litres mixed batch output.
- All models capable of mixing at a rate of 12 batches per hour giving production output rates ranging from 1.2 to 2.4 cubic metres per hour.
- Robustly engineered with fully enclosed drivelines, WINGET mixers provide safe, reliable performance and long service life.
- Highly efficient, two piece heavy gauge, spun steel drum.
- Multi-position lockable drum.
- Positive, heavy duty driveline using roller chain, (belt drive on electric start) bevel wheel and pinion.
- Fast Tow trailer models available with adjustable towbar, pneumatic tyres, mudguards and independent suspension.



Capacities:		Engine	Dimensions	
Mixed Batch Output	150 Litres	Yanmar L48 Electric start	Length o/a	1.65m
Unmixed Capacity	200 Litres		Width o/a	0.93m
Gross Drum Volume	362 Litres		Height o/a	1.71m
Drum Speed	22 rev/min		Loading Height	1.10m
Production Rate	1.8m3 / hr		Discharge Height	0.57m
			Machine Weight	410 kg

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Tel: 01392 882220

Email: office@pesplant.co.uk