



PES

PLANT SALES & PARTS

WINGET 200TM - Electric

General Information

- Materials loaded using a hydraulic loading hopper to ensure high production rates.
- High capacity mixer capable of producing up to 20 batches (4 cubic metres) per hour.
- Jacking system allows wheel removal to storage during long term use.
- 38 litre water reservoir with manually controlled filling and measured quantity discharge.
- Outrigger legs maintain stability throughout the loading cycle.
- Positive heavy duty driveline using roller chain bevel wheel and pinion.



Capacities:

Mixed Batch Output	200 Litres
Unmixed Capacity	285 Litres
Gross Drum Volume	485 Litres
Drum Speed	22 rev/min
Max Production Rate	4 m ³ /hr
Dragline Shovel Capacity	140 Litres

Power unit

Electric Motor
415volt, 3 phase,
50hz, 5.5hp

Dimensions

Length o/a	2.36m
Width o/a	2.91m
Hopper Width	1.21m
Height to top water tank	2.26m
Height c/w dragline feeder	2.98m
Discharge Height	0.79m
Height – hopper raised	2.97m
Ground Clearance – hopper	0.12m
Hopper loading height	0.49m

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Tel : 01392 882220

Email: office@pesplant.co.uk