



PLES

PLANT SALES & PARTS

WINGET 300R - Diesel

General Information

- Heavy Duty, reversing drum, mechanically fed concrete mixer manufactured to the highest specification.
- High capacity mixer capable of producing up to 24 batches (300R- 7.2 cubic metres, 400R-9.6 cubic metres, 500R-12 cubic metres) per hour.
- Jacking system allows wheel removal to storage during long term use.
- Towable chassis with four pneumatic tyred wheels.
- Standard machine includes water tank with automatic filling and measured volume discharge, or flowmeter.
- Mixer shown include optional batchweigher.



Capacities:

Mixed Batch Output	300 Litres
Unmixed Capacity	400 Litres
Gross Drum Volume	1600 Litres
Drum Speed	14 rev/min
Max Production Rate	7.2 m3/hr
Dragline Shovel Capacity	140 Litres

Power unit

Lister Petter
TR2

Dimensions

Length o/a hopper down	3.33m
Width o/a hopper width	1.82m
Hopper Width	1.50m
Height to top water tank	3.14m
Height top dragline feeder jib	4.88m
Discharge Height	1.37m
Height hopper raised	3.77m
Ground Clearance – hopper	0.10m
Hopper loading height	0.52m
Machine Weight	2325kg

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Tel : 01392 882220

Email: office@pesplant.co.uk