

WINGET 500R - Diesel

General Information

- Heavy Duty, reversing drum, mechanically fed concrete mixer manufactured to the highest specification.
- High capacity mixer capable of producing up to 24 batches (300R-7.2 cubic metres, 400R-9.6 cubic metres, 500R-12 cubic metres) per hour.
- Jacking system allows wheel removal to storage during long term
 use
- Towable chassis with four pneumatic tyred wheels.
- Standard machine includes water tank with automatic filling and measured volume discharge, or flowmeter.
- Mixer shown include optional batchweigher.



Capacities:		Power unit	Dimensions	
Mixed Batch Output	500 Litres	Lister Petter	Length o/a hopper down	4.14m
Unmixed Capacity	750 Litres	TR3	Width o/a hopper width	1.82m
Gross Drum Volume	3200 Litres		Hopper Width	1.50m
Drum Speed	14 rev/min		Height to top water tank	3.23m
Max Production Rate	12 m3/hr		Height top dragline feeder jib	4.88m
Dragline Shovel Capacity 140 Litres			Discharge Height	1.37m
			Height hopper raised	3.96m
			Ground Clearance – hopper	0.10m
			Hopper loading height	0.52m
			Machine Weight	2610kg

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Tel: 01392 882220

Email: office@pesplant.co.uk