

PLANT SALES & PARTS

WINGET 500R - Electric

General Information

- Heavy Duty, reversing drum, mechanically fed concrete mixer manufactured to the highest specification.
- High capacity mixer capable of producing up to 24 batches (300R-7.2 cubic metres, 400R-9.6 cubic metres, 500R-12 cubic metres) per hour.
- Jacking system allows wheel removal to storage during long term use.
- Towable chassis with four pneumatic tyred wheels.
- Standard machine includes water tank with automatic filling and measured volume discharge, or flowmeter.
- Mixer shown include optional batchweigher.



2610kg

| Capacities: | | Power unit | Dimensions | |
|-------------------------------------|-------------|-------------------|--------------------------------|-------|
| Mixed Batch Output | 500 Litres | Electric Motor | Length o/a hopper down | 4.14m |
| Unmixed Capacity | 750 Litres | 415 volt, 3 phase | Width o/a hopper width | 1.82m |
| Gross Drum Volume | 3200 Litres | 50hz, 20hp | Hopper Width | 1.50m |
| Drum Speed | 14 rev/min | | Height to top water tank | 3.23m |
| Max Production Rate | 12 m3/hr | | Height top dragline feeder jib | 4.88m |
| Dragline Shovel Capacity 140 Litres | | | Discharge Height | 1.37m |
| | | | Height hopper raised | 3.96m |
| | | | Ground Clearance – hopper | 0.10m |
| | | | Hopper loading height | 0.52m |

Plant & Engineering Services, Beare, Nr Exeter, Devon EX5 3JX

Machine Weight

Tel: 01392 882220

Email: office@pesplant.co.uk